

MACHINE DESCRIPTION	CAPACITY
Haas SL-30 CNC Lathe 10" & 15" Chuck, 34" Cutting Length, 3400 rpm.	39" between centers, 18" diameter
Haas SL-30 CNC Lathe 10" & 15" Chuck, 34" Cutting Length, 3400 rpm.	39" between centers, 18" diameter
Haas SL-20 CNC Lathe 8.3" Chuck, 20" Cutting Length, 4000 rpm.	24" between centers, 9" diameter
(2) Haas VF-2 CNC Mill High Speed Milling Center, 24 Tooling Index, 10,000 rpm Spindle. 1000" per min. Rapid Travel, Extended Memory. Z Capacity 20", Renishaw Probe	(X) 20" x (Y) 16" x (Z) 20"
Haas VF-3 CNC Mill High Speed Milling Center. 24 Tooling Index, 7500 rpm Spindle. 1000" per min. Rapid Travel, Extended Memory. Z Capacity 20"	(X) 40" x (Y) 20" x (Z) 20"
Haas VF-3 CNC Mill High Speed Milling Center. 24 Tooling Index, 10,000 rpm Spindle. 1000" per min. Rapid Travel, Extended Memory. Z Capacity 20", Renishaw Probe	(X) 40" x (Y) 20" x (Z) 20"
Haas VF-4SS CNC Mill High Speed Milling Center. 24 Tooling Index, 10,000 rpm Spindle. 1000" per min. Rapid Travel, Extended Memory. Z Capacity 23", Renishaw Probe"	(X) 50" x (Y) 22" x (Z) 23"
Leadwell V-40iT 5 axis machining center 24 Tooling Index, 10,000 rpm Spindle. 1417" per min. Rapid Travel, Extended Memory. Z Capacity 20", Renishaw Probe	(X) 33" x (Y) 25" x (Z) 19.2"
Fanuc Wire EDM Series 31i-WA 400	(X) 15.7 x (Y) 11.8 x (Z) 10.2" Thick
Fanuc Wire EDM Series 31i-WA 900	(X) 23.6 x (Y) 15.7 x (Z) 12.2" Thick
4" Giddings & Lewis 340-T Boring Mill Table 48" x 96"	(X) 86" x (Y) 54" x (Z) 58"
Bridgeport Series I 2 H.P. Variable Speed Vertical Milling Machine, 2 Axis Anilam Digital Readout, 7" Riser on column, Power Drawbar, Mounted with 11"x11" Advance Cross Slide Rotary Table	(X) 42" x (Y) 9"
Bridgeport Series I 2 H.P. Variable Speed Vertical Milling Machine, 2 Axis Tri-Onics 50 Digital Readout; Inventory of 3	(X) 42" x (Y) 9"
Bridgeport 1 H.P. J-Head Vertical Milling Machine, 2 Axis Tri-Onics Digital Readout	(X) 42" x (Y) 9"
No. 32-60 Rotary Blanchard Grinder , Coolant, 60 H.P. Spindle Drive	60" Magnetic x 24" / 66" Chuck,

Machine Description	CAPACITY
Okamoto DX Automatic Precision Grinder	12"x24"
Hydrabrasive Surface Grinder, Coolant	12"x18"
Gardner Six Eighteen Surface Grinder	6"x18"
Challenger Surface Grinder	6"x12"
DoAll Model C-6 Horizontal Metal cutting Band Saw, Roller Conveyor Infeed, Hydraulic	
Clausing Geared Head Engine Lathe, Model 1401, Full Length Threading, Taper Attachment	14"x46"
Shenwal Lathe	15"x40"
Sunnen MBBV-12900 Precision Honing Machine	
Carlton Radial Arm Drill Press, 4' Arm x 13" Column	4'x13"
DoAll Hand Feed Surface Grinder, Model DH-612	6"x12"
16" DoAll Vertical Metal cutting Band Saw, Tilt Table	16"
Harig Super 612	6"x12"
Sand Blast Cabinet	16"x19"x36"
Porter-Cable Belt Sander	6"
Oxy-Acetylene Torch Set	
325 Amp. Lincoln Idealarc Wire Feed Arc Welder,	